

IN THE CLAIMS

Please amend the claims as follows:

1. (Previously Presented) A transfer mechanism for transferring an object to be processed, comprising:

- a casing for defining a transfer chamber under a vacuum state, the casing having a transfer port for transferring the object between the transfer chamber and an outside thereof;
- a guide rail substantially horizontally installed in the transfer chamber;
- a moving part including a moving body movably installed on the guide rail and a holding body for holding the object;
- a horizontally driving unit for moving the moving body of the moving part along the guide rail;
- a position detecting linear scale installed on the moving part and extending in a moving direction of the moving part; and
- a plurality of position detecting sensors installed at a height corresponding to the linear scale on an inner surface of the casing, the position detecting sensors being disposed in the moving direction of the moving part such that a distance between two neighboring position detecting sensors is shorter than a length of the linear scale.

2. (Previously Presented) The transfer mechanism of claim 1, wherein the moving part further includes a supporting member for vertically movably connecting the holding body to the moving body, and

the transfer mechanism further includes an elevation mechanism for raising and lowering the supporting member with respect to the moving body.

3. (Previously Presented) The transfer mechanism of claim 2, wherein a horizontally transferring unit for moving the object only in a horizontal direction through the transfer port is installed in the outside of the casing; and

the elevation mechanism performs a positioning of the object held in the holding body to a height corresponding to the horizontally transferring unit.

4. (Previously Presented) The transfer mechanism of claim 2, wherein the moving body includes a stopper for restricting the lowest position of the supporting member and moves while the supporting member is at the lowest position thereof.

5. (Previously Presented) The transfer mechanism of claim 2, wherein the elevation mechanism includes:

a push rod extending through a bottom portion of the casing and making a contact with the supporting member;

a vertically driving unit disposed in the outside of the casing, for raising and lowering the push rod; and

a sealing unit for airtightly sealing a gap between the push rod and the casing.

6. (Original) The transfer mechanism of claim 1, wherein the horizontally driving unit is a linear motor mechanism including armature coils installed in the casing along the moving direction of the moving body and a field magnet installed on the moving body; and

a separation wall for airtightly separating the armature coil from the inside of the transfer chamber is installed in the casing.

7. (Original) The transfer mechanism of claim 1, further comprising a magnetic levitation device for levitating the moving body from the guide rail.

8. (Original) The transfer mechanism of claim 1, further comprising a gas jetting levitation device for levitating the moving body from the guide rail.

9. (Previously Presented) The transfer mechanism of claim 2, wherein a partition wall for dividing the transfer chamber into an upper portion and a lower portion is installed in the casing;

the holding body of the moving part is disposed in the upper portion of the transfer chamber while the moving body of the moving part is disposed in the lower portion of the transfer chamber;

the partition wall has a slit for allowing the supporting member of the moving part to move therethrough; and

the transfer mechanism further includes:

a gas supplying system for supplying an inactive gas to the upper portion of the transfer chamber, and

a gas exhausting system for evacuating the gas from the lower portion of the transfer chamber.

10. (Canceled)

11. (Previously Presented) A processing system comprising:

(a) a main transfer mechanism including:

a casing for defining a main transfer mechanism under a vacuum state, the casing having a plurality of transfer ports;

a guide rail substantially horizontally installed inside the transfer chamber under the vacuum state;

a moving body movably installed on the guide rail;

a horizontally driving unit for moving the moving body along the guide rail;

an elevation supporting structure having a holding body for holding an object to be processed and a supporting member for vertically movably connecting the holding body to the moving body; and

an elevation mechanism for raising and lowering the supporting member of the elevation supporting structure with respect to the moving body;

(b) an auxiliary transfer mechanism including a casing for defining an auxiliary transfer chamber under a vacuum state which selectively communicates with the main transfer chamber; and an auxiliary transfer unit installed in the auxiliary transfer chamber;

(c) a load-lock mechanism including a casing for defining a load-lock chamber which selectively communicates with the auxiliary transfer chamber and is selectively evacuated;

(d) an entrance transfer mechanism including a casing for defining an entrance transfer chamber under an atmospheric state which selectively communicates with the load-lock chamber; and an entrance transfer unit installed in the entrance transfer chamber;

(e) a cassette station connected to the entrance transfer chamber, for mounting therein a cassette container which accommodates a plurality of objects to be processed;

(f) a plurality of individual transfer mechanisms installed to correspond to the respective transfer ports of the main transfer mechanism, each of the individual transfer mechanisms including a casing for defining an individual transfer chamber under a vacuum state which selectively communicates with the main transfer chamber via the corresponding transfer port; and an individual transfer unit installed in the individual transfer chamber; and

(g) a plurality of processing apparatuses installed to correspond to the respective individual transfer mechanisms, each of the processing apparatuses including a casing for defining a vacuum processing chamber which selectively communicates with the corresponding individual transfer chamber, and performing a predetermined process on the object therein.

12. (Original) The processing system of claim 11, wherein the casing of the main transfer mechanism includes at least one of a plurality of casing segments connectable with each other, each of the casing segments having at least one of the transfer ports; and

the guide rail includes at least one of a plurality of guide rail segments connectable with each other.

13. (Previously Presented) A processing system comprising:

(a) a main transfer mechanism including:

a casing for defining a main transfer mechanism under a vacuum state, the casing having a plurality of transfer ports;

a guide rail substantially horizontally installed inside the transfer chamber under the vacuum state;

a moving part having a moving body movably installed on the guide rail and a holding body for holding an object to be processed;

a horizontally driving unit for moving the moving body of the moving part along the guide rail; and

a plurality of position detecting sensors for detecting the position of the moving part, the position detecting sensors being disposed in the casing in a moving direction of the moving part such that neighboring position detecting sensors are spaced from each other;

(b) an auxiliary transfer mechanism including a casing for defining an auxiliary transfer chamber under a vacuum state which selectively communicates with the main transfer chamber; and an auxiliary transfer unit installed in the auxiliary transfer chamber;

(c) a load-lock mechanism including a casing for defining a load-lock chamber which selectively communicates with the auxiliary transfer chamber and is selectively evacuated;

(d) an entrance transfer mechanism including a casing for defining an entrance transfer chamber under an atmospheric state which selectively communicates with the load-lock chamber; and an entrance transfer unit installed in the entrance transfer chamber;

(e) a cassette station connected to the entrance transfer chamber, for mounting therein a cassette container which accommodates a plurality of objects to be processed;

(f) a plurality of individual transfer mechanisms installed to correspond to the respective transfer ports of the main transfer mechanism, each of the individual transfer mechanisms including a casing for defining an individual transfer chamber under a vacuum state which selectively communicates with the main transfer chamber via the corresponding transfer port; and an individual transfer unit installed in the individual transfer chamber; and

(g) a plurality of processing apparatuses installed to correspond to the respective individual transfer mechanisms, each of the processing apparatuses including a casing for

defining a vacuum processing chamber which selectively communicates with the corresponding individual transfer chamber, and performing a predetermined process on the object therein.

14-18. (Canceled)

19. (Previously Presented) A transfer mechanism for transferring an object to be processed, comprising:

a casing for defining a transfer chamber under a vacuum state, the casing having a transfer port for transferring the object between the transfer chamber and an outside thereof;

a guide rail substantially horizontally installed inside the transfer chamber under the vacuum state;

a moving part including a moving body movably installed on the guide rail and a holding body for holding the object;

a horizontally driving unit for moving the moving body of the moving part along the guide rail; and

a plurality of position detecting sensors for detecting the position of the moving part, the position detecting sensors being disposed in the casing in a moving direction of the moving part such that neighboring position detecting sensors are spaced from each other,

wherein the moving part further includes a supporting member for vertically movably connecting the holding body to the moving body, and the transfer mechanism further includes an elevation mechanism for raising and lowering the supporting member with respect to the moving body, and

wherein the transfer mechanism further comprises:

a position detecting linear scale installed on at least one of the moving body, the holding body and the supporting member and extending in the moving direction of the moving body,

wherein the position detecting sensors are installed at a height corresponding to the linear scale on an inner surface of the casing, the position detecting sensors being disposed in the moving direction of the moving body such that a distance between two neighboring position detecting sensors is shorter than a length of the linear scale.

Application No. 10/500,102

Reply to Office Action dated February 25, 2009 and Advisory Action dated June 12, 2009

20-30(Canceled)